


LEDGE – model: WS-14

LED Vanity/Sconce Luminaire




WS-W1412



WS-1424



WS-1436



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

A luminous architectural profile and superior construction make this sconce appropriate for transitional and contemporary interiors or exteriors. Mitered silk-screened glass encases a maximum number of LEDs engineered for optimal illumination. Two sizes allow for cohesive specifications across residential and commercial applications.

FEATURES

- ETL & cETL listed for damp locations
- ADA compliant, low profile design
- 277V option available *special order*
- Replaceable LED module
- 50,000 hour rated life
- Color Temp: 3000K 2700K / 3500K available *special order*
- CRI: 90

SPECIFICATIONS

Construction: Aluminum with white mitered glass.

Power: Transformer located in outlet box. 120V input.

Light Source: High output LED.

Dimming: Dims to 10% with an electronic low voltage (ELV) dimmer.

Mounting: Mounts directly to junction box.

Finish: Brushed Aluminum (AL), Black (BK), Bronze (BZ), Graphite (GH)

Standards: ETL & cETL listed. ADA compliant.

Model	Length	Watt	Voltage	LED Lumens	Delivered Lumens	Finish
WS-W1412	12"	29W	120V	1200	690	AL <i>Brushed Aluminum</i>
						BK <i>Black</i>
						BZ <i>Bronze</i>
						GH <i>Graphite</i>
WS-1424	24"	55W	120V	2880	1455	AL <i>Brushed Aluminum</i>
						BZ <i>Bronze</i>
WS-1436	36"	91W	120V	4566	2235	BZ <i>Bronze</i>



Example: **WS-1424-AL**

For 277V special order, add an "F" before the finish: **WS-W1436F-BZ**
 For 2700K add "-27"; 3500K add "-35" before the finish: **WS-W1424-35-AL**

modernforms.com
 Phone (800) 526.2588
 Fax (800) 526.2585

Headquarters/Eastern Distribution Center
 44 Harbor Park Drive
 Port Washington, NY 11050

Central Distribution Center
 1600 Distribution Ct
 Lithia Springs, GA 30122

Western Distribution Center
 1750 Archibald Avenue
 Ontario, CA 91760