



# BLINC – model: WS-556

## LED Interior Sconce



Fixture Type:

Catalog Number:

Project: \_\_\_\_\_

Location: \_\_\_\_\_

### PRODUCT DESCRIPTION

A curved, whimsical and simple design. Blinc creates pleasing wall illumination from an adjustable sconce perched on a swivel with directional up and down lighting for a variety of applications. Display in clusters as a work of art. Full range dimming available. Perfect for residential and hospitality applications.

### FEATURES

- CEC Title 24 Compliant
- Up & down light
- ADA compliant, not when adjusted
- ETL & cETL Wet location IP65 listed for exterior (White finish)
- ETL & cETL damp location listed (Brushed Aluminum finish)
- Aluminum shade rotates 360° and adjustable tilts
- No transformer or driver required
- Full range dimming when used with compatible dimmers\*
- 277V option available (special order)
- 70,000 hour rated life
- Color Temp: 3000K
- CRI: 90

### SPECIFICATIONS

**Construction:** Aluminum

**Light Source:** High output LED.

**Finish:** Brushed Aluminum (AL)

**Standards:** ETL & cETL damp location listed. ADA compliant when not adjusted. CEC Title 24.

### ORDER NUMBER

|                     | Listing     | Wattage | Voltage | LED Lumens | Delivered Lumens | Finish           |  |
|---------------------|-------------|---------|---------|------------|------------------|------------------|--|
| <b>WS-55607-AL</b>  | <i>Damp</i> | 9W      | 120V    | 650        | 210              | Brushed Aluminum |  |
| <b>WS-W55607-WT</b> | <i>Wet</i>  | 9W      | 120V    | 650        | 210              | White            |  |

Example: **WS-W55607-WT**

For 277V special order, add an "F" before the finish: **WS-W55607F-WT**

modernforms.com  
Phone (800) 526.2588  
Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
44 Harbor Park Drive  
Port Washington, NY 11050

Central Distribution Center  
1600 Distribution Ct  
Lithia Springs, GA 30122

Western Distribution Center  
1750 Archibald Avenue  
Ontario, CA 91760