


**WOODY** 60" Ceiling Fan  
FR-W1814-60L

MODERN FORMS  
SMART FANS



**PRODUCT DESCRIPTION**

With sturdy blades crafted from solid wood- properly treated to weather the outdoors- this smart fan is rugged refinement to the core. Take control of it with our exclusive Modern Forms app- features like Adaptive Learning make life easier every day by suggesting optimized schedules, while a powerful DC motor inside keeps things running smooth, quiet and up to 70% more efficient than traditional AC fans. Choose a bronze housing with dark walnut wood, matte black with distressed koa or graphite with weathered gray.

**SPECIFICATIONS**

- Construction:** Aluminum
- Blade:** 13° Pitch, 60" sweep, ABS
- Downrod:** 1" O.D. x 4.5"H included
- Mounting Slope:** Up to 30°
- Lead Wire:** 80"
- Hanging Weight:** 19 lbs
- Total Power:** 61.5W
- Standards:** ETL/cETL Wet Location listed

**FEATURES**

- 6 fan speeds through both Summer and Winter Modes
- Silent DC motor
- Optional LED light kit included
- Includes RF wall control
- Additional RF wall control for 3, 4-way control sold separately
- Compatible with Modern Forms app

**LIGHT KIT PERFORMANCE**

- Light Source:** LED
- Light Wattage:** 19.5
- Dimming:** Integrated
- Color Temperature:** 3000K
- Rated Life:** 50,000 Hours
- Standards:** Title 24 JA8-2016 compliant

**ESTIMATED AIR PERFORMANCE**

- Airflow:** 8840 cubic ft per minute on high
- Power:** 42 watts on high
- Airflow Efficiency:** 209 cubic ft per minute per watt
- Revolutions Per Minute:** 152 RPMs on high/93 RPMs on average

**WIRELESS PERFORMANCE**

- RF Pairing Distance:** Up to 30 ft from fan
- Wi-Fi Range:** Up to 150 ft\*

**ORDER NUMBER**

Model	LED Lumens	Delivered Lumens	Housing	Blade
FR-W1814-60L	1600	887	<b>BZ</b> <i>Bronze</i>	<b>DW</b> <i>Dark Walnut</i>
			<b>GH</b> <i>Graphite</i>	<b>WG</b> <i>Weathered Gray</i>
			<b>MB</b> <i>Matte Black</i>	<b>DK</b> <i>Distressed Koa</i>

Example: **FR-W1814-60L-GH/MW**

\*Results may vary based on application and surroundings.



modernforms.com  
Phone (866) 810.6615  
Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
44 Harbor Park Drive  
Port Washington, NY 11050






Central Distribution Center  
1600 Distribution Ct  
Lithia Springs, GA 30122

Western Distribution Center  
1750 Archibald Avenue  
Ontario, CA 91760

**WOODY** 60" Ceiling Fan  
FR-W1814-60L

MODERN FORMS  
SMART FANS

**OPTIONAL ACCESSORIES**

	<b>F-WC</b>	<b>WT</b> White	Control fan speed, light brightness and switch between Summer and Winter Modes from up to 30 ft away. One RF Wall control comes standard with each Modern Forms Smart fan.
	<b>F-TS</b>	<b>BK</b> Black <b>WT</b> White	Sold separately. Android tablet comes pre-loaded with Modern Forms app, Wi-Fi range up to 150 ft from router. Results may vary based on application/surroundings.
	<b>XF-12</b> 12in <b>XF-18</b> 18in <b>XF-24</b> 24in <b>XF-36</b> 36in <b>XF-48</b> 48in <b>XF-60</b> 60in <b>XF-72</b> 72in	<b>AS</b> Automotive Silver <b>BZ</b> Bronze <b>CFI</b> Carbon Fiber** <b>DW</b> Dark Walnut <b>GB</b> Gloss Black <b>GH</b> Graphite <b>GW</b> Gloss White <b>MB</b> Matte Black <b>MW</b> Matte White <b>OB</b> Oil Rubbed Bronze <b>SS</b> Stainless Steel <b>TT</b> Titanium Silver	All our downrods are 1" O.D. and are threaded on the motor end to create an extra layer of security and allow for adjustments in the field.
	<b>XF-I</b>		Connects two downrods together.
	<b>XF-SCK</b>		Designed to accommodate buildings with steeper sloped ceilings up to 45° or 12/12 pitch.

Examples: RF Wall Control - **F-WC-WT**, Wi-Fi Touch Panel - **F-TS-WT**, Downrod - **XF-12-BZ**, Downrod Coupler - **XF-I-BZ**, Sloped Ceiling Kit - **XF-SCK-DW**

**NOTE:** Recommended maximum downrod length of 72" with 80" lead wire.

\*\*Carbon Fiber downrods available in 12", 18", 24" and 36"

**SUGGESTED DOWNROD HEIGHT USAGE**

<b>Ceiling Height</b>	15'	14'	13'	12'	11'	10'	9'
<b>Downrod</b>	72"	60"	48"	36"	24"	18"	12"

**SLOPED CEILING DEGREE CONVERSION CHART**

<b>Degree</b>	4-8°	9-13°	14-17°	18-21°	22-25°	26-29°	30-32°	33-35°	36-38°	39-41°	42-44°	45°
<b>Ceiling Slope Pitch</b>	1/12 pitch	2/12 pitch	3/12 pitch	4/12 pitch	5/12 pitch	6/12 pitch	7/12 pitch	8/12 pitch	9/12 pitch	10/12 pitch	11/12 pitch	12/12 pitch

Supplied mounting brackets allow mounting on ceiling slopes up to 30° (7/12 pitch). Optional slope kit allows mounting on ceilings up to 45° (12/12 pitch). The receiver will mount inside canopy up to 45°.

modernforms.com  
Phone (866) 810.6615  
Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
44 Harbor Park Drive  
Port Washington, NY 11050

Central Distribution Center  
1600 Distribution Ct  
Lithia Springs, GA 30122

Western Distribution Center  
1750 Archibald Avenue  
Ontario, CA 91760