


HYDRA 80" Ceiling Fan

FR-W1805-80L

MODERN FORMS SMART FANS



PRODUCT DESCRIPTION

As its name suggests, Hydra is all about water. Like all of our smart fans, it's wet-rated for outdoor use so you can maintain the continuity of your décor inside and out. Even with an impressive 120" blade sweep, this epically scaled smart fan moves a massive amount of air without consuming much energy, thanks to a powerful DC motor that runs up to 70% more efficient than AC motors. Control it all with our exclusive Modern Forms app. Available in 80 inches, 96 inches and 120 inches.

SPECIFICATIONS

- Construction:** Aluminum
- Blade:** 14° Pitch, 80" sweep, extruded aluminum
- Downrod:** 1" O.D. x 6"H included
- Mounting Slope:** Up to 30°
- Lead Wire:** 80"
- Hanging Weight:** 39 lbs
- Total Power:** 65.5W
- Standards:** ETL/cETL Wet Location listed

FEATURES

- 6 fan speeds through both Summer and Winter Modes
- Silent DC motor
- Optional LED light kit included
- Includes RF wall control
- Additional RF wall control for 3, 4-way control sold separately
- Compatible with Modern Forms app

LIGHT KIT PERFORMANCE

- Light Source:** LED
- Light Wattage:** 23.5W
- Dimming:** Integrated
- Color Temperature:** 3000K (2700K / 3500K options available)
- Rated Life:** 50,000 Hours
- Standards:** Title 24 JA8-2016 Compliant

ESTIMATED AIR PERFORMANCE

- Airflow:** 11308 cubic ft per minute on high
- Power:** 42 watts on high
- Airflow Efficiency:** 270 cubic ft per minute per watt
- Revolutions Per Minute:** 88 RPMs on high

WIRELESS PERFORMANCE

- RF Pairing Distance:** Up to 30 ft from fan
- Wi-Fi Range:** Up to 150 ft*


ORDER NUMBER

Model	LED Lumens	Delivered Lumens	Housing	Blade
FR-W1805-80L	2041	1013	BZ <i>Bronze</i>	<i>Bronze</i>
			TT <i>Titanium Silver</i>	<i>Titanium Silver</i>

Example: **FR-W1805-80L-BZ**

For 2700K add "-27"; 3500K add "-35" before the finish: **FR-W1805-80L-27-TT**

*Results may vary based on application and surroundings.



modernforms.com
Phone (866) 810.6615
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122






Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760

HYDRA 80" Ceiling Fan

FR-W1805-80L

MODERN FORMS SMART FANS

OPTIONAL ACCESSORIES

RF Wall Control 	F-WC	WT White Control fan speed, light brightness and switch between Summer and Winter Modes from up to 30 ft away. One RF Wall control comes standard with each Modern Forms Smart fan.
RF Remote Control	F-RC	WT White Sold separately. Control fan speed and light brightness, and switch between Summer and Winter Modes from up to 50 ft away. Includes easy-to-install cradle and batteries.
Wi-Fi Touch Panel Wall Control 	F-TS	BK Black WT White Sold separately. Android tablet comes pre-loaded with Modern Forms app, Wi-Fi range up to 150 ft from router. Results may vary based on application/surroundings.
Downrod 	XF-12 12in XF-18 18in XF-24 24in XF-36 36in XF-48 48in XF-60 60in XF-72 72in	AS Automotive Silver BA Brushed Aluminum BZ Bronze CFI Carbon Fiber** DW Dark Walnut All our downrods are 1" O.D. and are threaded on the motor end to create an extra layer of security and allow for adjustments in the field.
Downrod Couplers 	XF-I	GB Gloss Black GH Graphite GW Gloss White KO Koa† Connects two downrods together.
Sloped Ceiling Kit 	XF-SCK	MB Matte Black Matte MW White OB Oil Rubbed Bronze SS Stainless Steel TT Titanium Silver Designed to accommodate buildings with steeper sloped ceilings up to 45° or 12/12 pitch.

Examples: RF Wall Control - **F-WC-WT**, RF Remote Control - **F-RC-WT**, Wi-Fi Touch Panel - **F-TS-WT**, Downrod - **XF-12-BZ**, Downrod Coupler - **XF-I-BZ**, Sloped Ceiling Kit - **XF-SCK-DW**

SUGGESTED DOWNROD HEIGHT USAGE

Ceiling Height	15'	14'	13'	12'	11'	10'	9'
Downrod	72"	60"	48"	36"	24"	18"	12"

SLOPED CEILING DEGREE CONVERSION CHART

Degree	4-8°	9-13°	14-17°	18-21°	22-25°	26-29°	30-32°	33-35°	36-38°	39-41°	42-44°	45°
Ceiling Slope Pitch	1/12 pitch	2/12 pitch	3/12 pitch	4/12 pitch	5/12 pitch	6/12 pitch	7/12 pitch	8/12 pitch	9/12 pitch	10/12 pitch	11/12 pitch	12/12 pitch

Supplied mounting brackets allow mounting on ceiling slopes up to 30° (7/12 pitch). Optional slope kit allows mounting on ceilings up to 45° (12/12 pitch). The receiver will mount inside canopy up to 45°.

NOTE: Recommended maximum downrod length of 72" with 80" lead wire

**Carbon Fiber downrods available in 12", 18", 24" and 36"

†Koa downrods available in 12", 18", 24" and 36"

modernforms.com
Phone (866) 810.6615
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760