


# NAUTILUS 56" Ceiling Fan

FR-W1818-56L

## MODERN FORMS SMART FANS



### PRODUCT DESCRIPTION

With its elevated take on nautical style, this smart fan more than delivers on both form and function. Weathered wood-finished blades complement the polish of oil-rubbed bronze or graphite housings, while the WAC-powered LED luminaire radiates beautifully through an optically enhanced Fresnel glass lens. The DC motor keeps the blades running quietly so you'll always hear the sound of the waves- whether they're steps from your porch or in an afternoon daydream.

### SPECIFICATIONS

**Construction:** Aluminum  
**Blade:** 13° Pitch, 56" sweep, ABS  
**Downrod:** 1" O.D. x 4.5"H included  
**Mounting Slope:** Up to 30°  
**Lead Wire:** 80"  
**Hanging Weight:** 23 lbs  
**Total Power:** 52.5W  
**Standards:** ETL/cETL Wet Location listed

### FEATURES

- 6 fan speeds through both Summer and Winter Modes
- Silent DC motor
- Luminaire cover not available
- Includes RF wall control
- Additional RF wall control for 3, 4-way control sold separately
- Compatible with Modern Forms app

### LIGHT KIT PERFORMANCE

**Light Source:** LED  
**Light Wattage:** 23.5W  
**Dimming:** Integrated  
**Color Temperature:** 3000K (2700K / 3500K options available)  
**Rated Life:** 50,000 Hours  
**Standards:** Title 24 JA8-2016 Compliant

### ESTIMATED AIR PERFORMANCE

**Airflow:** 7013 cubic ft per minute on high  
**Power:** 29 watts on high  
**Airflow Efficiency:** 245 cubic ft per minute per watt  
**Revolutions Per Minute:** 145 RPMs on high

### WIRELESS PERFORMANCE

**RF Pairing Distance:** Up to 30 ft from fan  
**Wi-Fi Range:** Up to 150 ft\*


### ORDER NUMBER

Model	LED Lumens	Delivered Lumens	Housing		Blade	
FR-W1818-56L	2041	1347	<b>GH</b>	Graphite	<b>WG</b>	Weathered Gray
			<b>OB</b>	Oil Rubbed Bronze	<b>DW</b>	Dark Walnut

Example: **FR-W1818-56L-GH/WG**

For 2700K add "27"; 3500K add "35" before finish: **FR-W1818-56L270BDW**

\*Results may vary based on application and surroundings.



modernforms.com  
 Phone (866) 810.6615  
 Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
 44 Harbor Park Drive  
 Port Washington, NY 11050

Central Distribution Center  
 1600 Distribution Ct  
 Lithia Springs, GA 30122






Western Distribution Center  
 1750 Archibald Avenue  
 Ontario, CA 91760

# NAUTILUS 56" Ceiling Fan

FR-W1818-56L

## MODERN FORMS SMART FANS

### OPTIONAL ACCESSORIES

<b>RF Wall Control</b> 	<b>F-WC</b>	<b>WT</b> White Control fan speed, light brightness and switch between Summer and Winter Modes from up to 30 ft away. One RF Wall control comes standard with each Modern Forms Smart fan.
<b>RF Remote Control</b>	<b>F-RC</b>	<b>WT</b> White Sold separately. Control fan speed and light brightness, and switch between Summer and Winter Modes from up to 50 ft away. Includes easy-to-install cradle and batteries.
<b>Wi-Fi Touch Panel Wall Control</b> 	<b>F-TS</b>	<b>BK</b> Black <b>WT</b> White Sold separately. Android tablet comes pre-loaded with Modern Forms app, Wi-Fi range up to 150 ft from router. Results may vary based on application/surroundings.
<b>Downrod</b> 	<b>XF-12</b> 12in <b>XF-18</b> 18in <b>XF-24</b> 24in <b>XF-36</b> 36in <b>XF-48</b> 48in <b>XF-60</b> 60in <b>XF-72</b> 72in	<b>AS</b> Automotive Silver <b>BA</b> Brushed Aluminum <b>BZ</b> Bronze <b>CFI</b> Carbon Fiber** <b>DW</b> Dark Walnut All our downrods are 1" O.D. and are threaded on the motor end to create an extra layer of security and allow for adjustments in the field.
<b>Downrod Couplers</b> 	<b>XF-I</b>	<b>GB</b> Gloss Black <b>GH</b> Graphite <b>GW</b> Gloss White <b>KO</b> Koa† Connects two downrods together.
<b>Sloped Ceiling Kit</b> 	<b>XF-SCK</b>	<b>MB</b> Matte Black Matte <b>MW</b> White <b>OB</b> Oil Rubbed Bronze <b>SS</b> Stainless Steel <b>TT</b> Titanium Silver Designed to accommodate buildings with steeper sloped ceilings up to 45° or 12/12 pitch.

Examples: RF Wall Control - **F-WC-WT**, RF Remote Control - **F-RC-WT**, Wi-Fi Touch Panel - **F-TS-WT**, Downrod - **XF-12-BZ**, Downrod Coupler - **XF-I-BZ**, Sloped Ceiling Kit - **XF-SCK-DW**

### SUGGESTED DOWNROD HEIGHT USAGE

Ceiling Height	15'	14'	13'	12'	11'	10'	9'
Downrod	72"	60"	48"	36"	24"	18"	12"

### SLOPED CEILING DEGREE CONVERSION CHART

Degree	4-8°	9-13°	14-17°	18-21°	22-25°	26-29°	30-32°	33-35°	36-38°	39-41°	42-44°	45°
Ceiling Slope Pitch	1/12 pitch	2/12 pitch	3/12 pitch	4/12 pitch	5/12 pitch	6/12 pitch	7/12 pitch	8/12 pitch	9/12 pitch	10/12 pitch	11/12 pitch	12/12 pitch

Supplied mounting brackets allow mounting on ceiling slopes up to 30° (7/12 pitch). Optional slope kit allows mounting on ceilings up to 45° (12/12 pitch). The receiver will mount inside canopy up to 45°.

**NOTE:** Recommended maximum downrod length of 72" with 80" lead wire

\*\*Carbon Fiber downrods available in 12", 18", 24" and 36"

†Koa downrods available in 12", 18", 24" and 36"

modernforms.com  
Phone (866) 810.6615  
Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
44 Harbor Park Drive  
Port Washington, NY 11050

Central Distribution Center  
1600 Distribution Ct  
Lithia Springs, GA 30122

Western Distribution Center  
1750 Archibald Avenue  
Ontario, CA 91760