


VENUS 60" Ceiling Fan

FR-W1920-60L

MODERN FORMS SMART FANS



PRODUCT DESCRIPTION

An otherworldly experience awaits with a silent DC motor so you can hear the leaves rustling outdoors or nothing at all inside. With our Modern Forms app, this smart fan can integrate with smart home devices you already own, and adaptively learn your desires to schedule its own activity and cut down on energy use.

SPECIFICATIONS

Construction: Aluminum
Blade: 14° Pitch, 60" sweep, ABS
Downrod: 1" O.D. x 4.5"H included
Mounting Slope: Up to 30°
Lead Wire: 80"
Hanging Weight: 19 lbs
Total Power: 37.5W
Standards: ETL/cETL Wet Location listed

FEATURES

- 6 fan speeds through both Summer and Winter Modes
- Silent DC motor
- Optional LED light kit included
- Includes RF wall control
- Additional RF wall control for 3, 4-way control sold separately
- Compatible with Modern Forms app

LIGHT KIT PERFORMANCE

Light Source: LED
Light Wattage: 19.5W
Dimming: Integrated
Color Temperature: 3000K (2700K / 3500K options available)
Rated Life: 50,000 Hours
Standards: Title 24 JA8-2016 Compliant

ESTIMATED AIR PERFORMANCE

Airflow: 7154 cubic ft per minute on high
Power: 18 watts on high
Airflow Efficiency: 397 cubic ft per minute per watt
Revolutions Per Minute: 145 RPMs on high

WIRELESS PERFORMANCE

RF Pairing Distance: Up to 30 ft from fan
Wi-Fi Range: Up to 150 ft*

ORDER NUMBER

Model	LED Lumens	Delivered Lumens	Housing	Blade
FR-W1920-60L	1600	1025	AB Aged Brass	BZ Bronze
			TT Titanium Silver	MW Matte White
			AV Antique Silver	MB Matte Black

Example: **FR-W1920-60L-TT/MW**

For 2700K add "27"; 3500K add "35" before the finish: **FR-W1920-60L-27-ABBZ**

*Results may vary based on application and surroundings.



modernforms.com
 Phone (866) 810.6615
 Fax (800) 526.2585

Headquarters/Eastern Distribution Center
 44 Harbor Park Drive
 Port Washington, NY 11050

Central Distribution Center
 1600 Distribution Ct
 Lithia Springs, GA 30122






Western Distribution Center
 1750 Archibald Avenue
 Ontario, CA 91760

VENUS 60" Ceiling Fan

FR-W1920-60L

MODERN FORMS SMART FANS

OPTIONAL ACCESSORIES

RF Wall Control  F-WC	WT White	Control fan speed, light brightness and switch between Summer and Winter Modes from up to 30 ft away. One RF Wall control comes standard with each Modern Forms Smart fan.
RF Remote Control F-RC	WT White	Sold separately. Control fan speed and light brightness, and switch between Summer and Winter Modes from up to 50 ft away. Includes easy-to-install cradle and batteries.
Wi-Fi Touch Panel Wall Control  F-TS	BK Black WT White	Sold separately. Android tablet comes pre-loaded with Modern Forms app, Wi-Fi range up to 150 ft from router. Results may vary based on application/surroundings.
Downrod  XF-12 12in XF-18 18in XF-24 24in XF-36 36in XF-48 48in XF-60 60in XF-72 72in	AS Automotive Silver BA Brushed Aluminum BZ Bronze CFI Carbon Fiber** DW Dark Walnut	All our downrods are 1" O.D. and are threaded on the motor end to create an extra layer of security and allow for adjustments in the field.
Downrod Couplers  XF-I	GB Gloss Black GH Graphite GW Gloss White KO Koa†	Connects two downrods together.
Sloped Ceiling Kit  XF-SCK	MB Matte Black Matte MW White OB Oil Rubbed Bronze SS Stainless Steel TT Titanium Silver	Designed to accommodate buildings with steeper sloped ceilings up to 45° or 12/12 pitch.

Examples: RF Wall Control - **F-WC-WT**, RF Remote Control - **F-RC-WT**, Wi-Fi Touch Panel - **F-TS-WT**, Downrod - **XF-12-BZ**, Downrod Coupler - **XF-I-BZ**, Sloped Ceiling Kit - **XF-SCK-DW**

SUGGESTED DOWNROD HEIGHT USAGE

Ceiling Height	15'	14'	13'	12'	11'	10'	9'
Downrod	72"	60"	48"	36"	24"	18"	12"

SLOPED CEILING DEGREE CONVERSION CHART

Degree	4-8°	9-13°	14-17°	18-21°	22-25°	26-29°	30-32°	33-35°	36-38°	39-41°	42-44°	45°
Ceiling Slope Pitch	1/12 pitch	2/12 pitch	3/12 pitch	4/12 pitch	5/12 pitch	6/12 pitch	7/12 pitch	8/12 pitch	9/12 pitch	10/12 pitch	11/12 pitch	12/12 pitch

Supplied mounting brackets allow mounting on ceiling slopes up to 30° (7/12 pitch). Optional slope kit allows mounting on ceilings up to 45° (12/12 pitch). The receiver will mount inside canopy up to 45°.

NOTE: Recommended maximum downrod length of 72" with 80" lead wire

**Carbon Fiber downrods available in 12", 18", 24" and 36"

†Koa downrods available in 12", 18", 24" and 36"

modernforms.com
Phone (866) 810.6615
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760