

FM-2111

Project:

Location:

Fixture Type:

Catalog Number:

AVAILABLE FINISHES:



Circa

FM-2111

PRODUCT DESCRIPTION

This utilitarian family features a range of sizes to accommodate compact spaces like narrow hallways and stairwell landings as well as medium-sized rooms in office buildings and luxuryhomes. A thick, one-inch glass shade is pressed and sanded for pure whiteness, while a second insert is layered inside to extract the optimal amount of light from the high-performanceLED modules.

FEATURES

- ACLED driverless technology
- Etched pressed glass diffuser with interior ceramic glaze
- 0-10V dimming option available (special order), unit dimensions: 3.4" x 1.2" x 0.5" (model#LDS065M010AFE-LO1)
- 277V option available for special order.
- 2700K and 3500K CCT option available for special order.

SPECIFICATIONS

Rated Life 54000 Hours

Standards ETL, cETL,Damp Location Listed,Title 24 JA8: 2019 Compliant,Energy

Star 2.0,ADA

Input 120 VAC,50/60Hz

Dimming ELV: 100-10%,TRIAC: 100-10%

Mounting Can be mounted on ceiling or wall in all orientations

 Color Temp
 3000K

 CRI
 90

Construction Steel construction with etched opal glass

REPLACEMENT PARTS

RPL-GLA-4111 - Glass

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
FM-2111 11"	3000K	BK Black	26W	2759	1080
	3000K	TT Titanium	26W	2759	1080


Example: FM-2111-30-TT

•For 277V special order, add an "F" before the finish: FM-2111F-30-BK

•For '3500K' add "-'35"';'2700K' add "-'27" before the finish: FM-2111-27-TT

For custom requests please contact customs@modernforms.com





FM-2115

Project:

Location:

Fixture Type:

Catalog Number:

AVAILABLE FINISHES:



Circa

FM-2115

PRODUCT DESCRIPTION

This utilitarian family features a range of sizes to accommodate compact spaces like narrow hallways and stairwell landings as well as medium-sized rooms in office buildings and luxuryhomes. A thick, one-inch glass shade is pressed and sanded for pure whiteness, while a second insert is layered inside to extract the optimal amount of light from the high-performanceLED modules.

FEATURES

- ACLED driverless technology
- Etched pressed glass diffuser with interior ceramic glaze
- 0-10V dimming option available (special order), unit dimensions: 3.4" x 1.2" x 0.5" (model#LDS065M010AFE-LO1)
- 2700K and 3500K CCT option available for special order.
- 277V option available for special order.

SPECIFICATIONS

Rated Life	54000 Hours				
Standards	ETL, cETL,Damp Location Listed,Title 24 JA8: 2019 Compliant,Energ				
	Star 2.0,ADA				
Input	120 VAC,50/60Hz				
Dimming	ELV: 100-10%,TRIAC: 100-10%				
Mounting	Can be mounted on ceiling or wall in all orientations				
Color Temp	3000K				
CRI	90				
Construction	Steel construction with etched opal glass				

REPLACEMENT PARTS

RPL-GLA-4115 - Glass

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
FM-2115 14"	3000K	BK Black	24.7W	2729	1463
	3000K	TT Titanium	24.7W	2729	1463

Example: FM-2115-30-TT

•For 277V special order, add an "F" before the finish: FM-2115F-30-TT

•For '2700K' add "-'27"';'3500K' add "-'35"' before the finish: FM-2115-35-BK

For custom requests please contact customs@modernforms.com