

WS-47919

i roject.	
Location:	
Fixture Type:	
Catalog Number:	

#### **AVAILABLE FINISHES:**



Project.



# Lightstick

WS-47919

#### PRODUCT DESCRIPTION

Modern and ultra-minimal. Lightstick is a slim LED vanity luminaire designed perfectly for residential, hospitality and commercial powder rooms. A slender bar of light constructed froma co-extrusion of clear and white acrylic affords the luxurious dimensional look of cased glass but durable enough for its dramatic proportions. The versatile design allows it to beplaced horizontally or vertically or even at angles on walls and ceilings.

# **FEATURES**

- ACLED driverless technology
- Co-extruded acrylic diffuser
- 1" slim junction box included and can be ordered separately (model# JB-0501)
- 0-10V dimming option available (special order), unit dimensions: 3.4" x 1.2" x 0.5" (model#LDS065M010AFE-LO1)
- Conversion plate included for 4" junction box
- Trimless spackle cover available for 4" square junction box recessed in drywall thicknesses of 1/2", 5/8", 1", and 1-1/4"; accessory not included and can be ordered separately (model# MKCP-3040-WT)

# **SPECIFICATIONS**

Rated Life	54000 Hours
Standards	ETL, cETL,Damp Location Listed,Title 24 JA8: 2019 Compliant,ADA
Input	120 VAC,50/60Hz
Dimming	ELV
Mounting	Can be mounted on ceiling or wall in all orientations
Color Temp	3000K
CRI	90
Construction	Aluminum hardware, co-extruded acrylic diffuser

#### REPLACEMENT PARTS

JB-0501 - 1" Slim Junction Box

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	<b>Delivered Lumens</b>
WS-47919 19"	3000K	AL Brushed Aluminum	16.8W	1268	975
	3000K	WT White	16.8W	1268	975

Example: WS-47919-WT



Project:

Location:

Fixture Type:

Catalog Number:

# **AVAILABLE FINISHES:**





# Lightstick

WS-47925

#### PRODUCT DESCRIPTION

Modern and ultra-minimal. Lightstick is a slim LED vanity luminaire designed perfectly for residential, hospitality and commercial powder rooms. A slender bar of light constructed froma co-extrusion of clear and white acrylic affords the luxurious dimensional look of cased glass but durable enough for its dramatic proportions. The versatile design allows it to beplaced horizontally or vertically or even at angles on walls and ceilings.

# **FEATURES**

- · ACLED driverless technology
- · Co-extruded acrylic diffuser
- 1" slim junction box included and can be ordered separately (model# JB-0501)
- 0-10V dimming option available (special order), unit dimensions: 3.4" x 1.2" x 0.5" (model#LDS065M010AFE-LO1)
- Conversion plate included for 4" junction box
- Trimless spackle cover available for 4" square junction box recessed in drywall thicknesses of 1/2", 5/8", 1", and 1-1/4"; accessory not included and can be ordered separately (model# MKCP-3040-WT)

# **SPECIFICATIONS**

54000 Hours
ETL, cETL,Damp Location Listed,Title 24 JA8: 2019 Compliant,ADA
120 VAC,50/60Hz
ELV
Can be mounted on ceiling or wall in all orientations
3000K
90
Aluminum hardware, co-extruded acrylic diffuser

#### REPLACEMENT PARTS

JB-0501 - 1" Slim Junction Box

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	<b>Delivered Lumens</b>
WS-47925 25"	3000K	AL Brushed Aluminum	22.4W	1708	1375
	3000K	WT White	22.4W	1708	1375

WS-47925

Example: WS-47925-WT



Project:

Location:

Fixture Type:

Catalog Number:

## **AVAILABLE FINISHES:**





# Lightstick

WS-47937

#### PRODUCT DESCRIPTION

Modern and ultra-minimal. Lightstick is a slim LED vanity luminaire designed perfectly for residential, hospitality and commercial powder rooms. A slender bar of light constructed froma co-extrusion of clear and white acrylic affords the luxurious dimensional look of cased glass but durable enough for its dramatic proportions. The versatile design allows it to beplaced horizontally or vertically or even at angles on walls and ceilings.

#### **FEATURES**

- · ACLED driverless technology
- · Co-extruded acrylic diffuser
- 1" slim junction box included and can be ordered separately (model# JB-0501)
- 0-10V dimming option available (special order), unit dimensions: 3.4" x 1.2" x 0.5" (model#LDS065M010AFE-LO1)
- Conversion plate included for 4" junction box
- Trimless spackle cover available for 4" square junction box recessed in drywall thicknesses of 1/2", 5/8", 1", and 1-1/4"; accessory not included and can be ordered separately (model# MKCP-3040-WT)

# **SPECIFICATIONS**

D-4--- 11:6-

Rated Life	54000 Hours
Standards	ETL, cETL,Damp Location Listed,Title 24 JA8: 2019 Compliant,ADA
Input	120 VAC,50/60Hz
Dimming	ELV
Mounting	Can be mounted on ceiling or wall in all orientations
Color Temp	3000K
CRI	90
Construction	Aluminum hardware, co-extruded acrylic diffuser

#### REPLACEMENT PARTS

JB-0501 - 1" Slim Junction Box

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	<b>Delivered Lumens</b>
WS-47937 37"	3000K	AL Brushed Aluminum	33.2W	2450	1949
	3000K	WT White	33.2W	2450	1949

WS-47937

Example: WS-47937-WT



Location:

Fixture Type:

Catalog Number:

## **AVAILABLE FINISHES:**



Project:



# Lightstick

WS-47949

#### PRODUCT DESCRIPTION

Modern and ultra-minimal. Lightstick is a slim LED vanity luminaire designed perfectly for residential, hospitality and commercial powder rooms. A slender bar of light constructed froma co-extrusion of clear and white acrylic affords the luxurious dimensional look of cased glass but durable enough for its dramatic proportions. The versatile design allows it to beplaced horizontally or vertically or even at angles on walls and ceilings.

#### **FEATURES**

- ACLED driverless technology
- · Co-extruded acrylic diffuser
- 1" slim junction box included and can be ordered separately (model# JB-0501)
- 0-10V dimming option available (special order), unit dimensions:  $3.4" \times 1.2" \times 0.5"$  (model#LDS065M010AFE-LO1)
- Conversion plate included for 4" junction box
- Trimless spackle cover available for 4" square junction box recessed in drywall thicknesses of 1/2", 5/8", 1", and 1-1/4"; accessory not included and can be ordered separately (model# MKCP-3040-WT)

# SPECIFICATIONS

Rated Life	54000 Hours
Standards	ETL, cETL,Damp Location Listed,Title 24 JA8: 2019 Compliant,ADA
Input	120 VAC,50/60Hz
Dimming	ELV
Mounting	Can be mounted on ceiling or wall in all orientations
Color Temp	3000K
CRI	90
Construction	Aluminum hardware, co-extruded acrylic diffuser

#### REPLACEMENT PARTS

JB-0501 - 1" Slim Junction Box

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	<b>Delivered Lumens</b>
WS-47949 49"	3000K	AL Brushed Aluminum	44W	3171	2479
	3000K	WT White	44W	3171	2479

WS-47949

Example: WS-47949-WT



Location:

Fixture Type:

Catalog Number:

## **AVAILABLE FINISHES:**



Project:

# Lightstick

WS-47961

#### PRODUCT DESCRIPTION

Modern and ultra-minimal. Lightstick is a slim LED vanity luminaire designed perfectly for residential, hospitality and commercial powder rooms. A slender bar of light constructed froma co-extrusion of clear and white acrylic affords the luxurious dimensional look of cased glass but durable enough for its dramatic proportions. The versatile design allows it to beplaced horizontally or vertically or even at angles on walls and ceilings.

#### **FEATURES**

- · ACLED driverless technology
- · Co-extruded acrylic diffuser
- 1" slim junction box included and can be ordered separately (model# JB-0501)
- 0-10V dimming option available (special order), unit dimensions: 3.4" x 1.2" x 0.5" (model#LDS065M010AFE-LO1)
- Conversion plate included for 4" junction box
- Trimless spackle cover available for 4" square junction box recessed in drywall thicknesses of 1/2", 5/8", 1", and 1-1/4"; accessory not included and can be ordered separately (model# MKCP-3040-WT)

# SPECIFICATIONS

Rated Life	54000 Hours
Standards	ETL, cETL,Damp Location Listed,Title 24 JA8: 2019 Compliant,ADA
Input	120 VAC,50/60Hz
Dimming	ELV
Mounting	Can be mounted on ceiling or wall in all orientations
Color Temp	3000K
CRI	90
Construction	Aluminum hardware, co-extruded acrylic diffuser

#### REPLACEMENT PARTS

JB-0501 - 1" Slim Junction Box

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	<b>Delivered Lumens</b>
WS-47961 61"	3000K	AL Brushed Aluminum	45.9W	3651	2826
	3000K	WT White	45.9W	3651	2826

WS-47961

Example: WS-47961-WT

WS-47973

Project:

Location:
Fixture Type:

Catalog Number:

## **AVAILABLE FINISHES:**





# Lightstick

WS-47973

#### PRODUCT DESCRIPTION

Modern and ultra-minimal. Lightstick is a slim LED vanity luminaire designed perfectly for residential, hospitality and commercial powder rooms. A slender bar of light constructed froma co-extrusion of clear and white acrylic affords the luxurious dimensional look of cased glass but durable enough for its dramatic proportions. The versatile design allows it to beplaced horizontally or vertically or even at angles on walls and ceilings.

#### **FEATURES**

- ACLED driverless technology
- · Co-extruded acrylic diffuser
- 1" slim junction box included and can be ordered separately (model# JB-0501)
- 0-10V dimming option available (special order), unit dimensions: 3.4" x 1.2" x 0.5" (model#LDS065M010AFE-LO1)
- Conversion plate included for 4" junction box
- Trimless spackle cover available for 4" square junction box recessed in drywall thicknesses of 1/2", 5/8", 1", and 1-1/4"; accessory not included and can be ordered separately (model# MKCP-3040-WT)

# **SPECIFICATIONS**

Rated Life	54000 Hours
Standards	ETL, cETL,Damp Location Listed,Title 24 JA8: 2019 Compliant,ADA
Input	120 VAC,50/60Hz
Dimming	ELV
Mounting	Can be mounted on ceiling or wall in all orientations
Color Temp	3000K
CRI	90
Construction	Aluminum hardware, co-extruded acrylic diffuser

#### REPLACEMENT PARTS

JB-0501 - 1" Slim Junction Box

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	<b>Delivered Lumens</b>
WS-47973 73"	3000K	AL Brushed Aluminum	66W	4900	3782
	3000K	WT White	66W	4900	3782

Example: WS-47973-WT

WS-47997

roject:			
ocation:			

Fixture Type:

Catalog Number:

## **AVAILABLE FINISHES:**





# Lightstick

WS-47997

#### PRODUCT DESCRIPTION

Modern and ultra-minimal. Lightstick is a slim LED vanity luminaire designed perfectly for residential, hospitality and commercial powder rooms. A slender bar of light constructed froma co-extrusion of clear and white acrylic affords the luxurious dimensional look of cased glass but durable enough for its dramatic proportions. The versatile design allows it to beplaced horizontally or vertically or even at angles on walls and ceilings.

# **FEATURES**

- ACLED driverless technology
- · Co-extruded acrylic diffuser
- 1" slim junction box included and can be ordered separately (model# JB-0501)
- 0-10V dimming option available (special order), unit dimensions: 3.4" x 1.2" x 0.5" (model#LDS065M010AFE-LO1)
- Conversion plate included for 4" junction box
- Trimless spackle cover available for 4" square junction box recessed in drywall thicknesses of 1/2", 5/8", 1", and 1-1/4"; accessory not included and can be ordered separately (model# MKCP-3040-WT)

# **SPECIFICATIONS**

54000 Hours
ETL, cETL,Damp Location Listed,Title 24 JA8: 2019 Compliant,ADA
120 VAC,50/60Hz
ELV
Can be mounted on ceiling or wall in all orientations
3000K
90
Aluminum hardware, co-extruded acrylic diffuser

#### REPLACEMENT PARTS

JB-0501 - 1" Slim Junction Box

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS-47997 97"	3000K	AL Brushed Aluminum	88W	6342	4874
	3000K	WT White	88W	6342	4874

Example: WS-47997-WT