



Project:

Location:

Fixture Type:

Catalog Number:

AVAILABLE FINISHES:



Open Bar

WS-52127

PRODUCT DESCRIPTION

A window of opportunity. This intriguing bath bar features an open design that allows light to shine through. A CCT switch enables multiple color temperature options to customize the look and feel of the room. Utilizing state of the art ACLED driverless technology, the versatile luminaire comes with an optional 1" junction box that allows it to be installed to your precise position in the orientation of your choice.

FEATURES

- ACLED driverless technology
- 1" slim junction box included and can be ordered separately (model# JB-0501)
- Built in color temperature adjustability. Switch from 2700K/3000K/3500K
- Conversion plate included to accommodate 4" junction box
- Trimless spackle cover available for 4" square junction box recessed in drywall thicknesses of 1/2", 5/8", 1", and 1-1/4"; accessory not included and can be ordered separately (model# MKCP-3040-WT)
- Option to pre-select color temperature or adjust in the field

SPECIFICATIONS

Rated Life	54000 Hours
Standards	ETL, cETL,Damp Location Listed,Title 24 JA8: 2019 Compliant
Input	120 VAC,50/60Hz
Dimming	ELV: 100-10%,TRIAC: 100-5%
Mounting	Can be mounted on ceiling or wall in all orientations
Color Temp	2700K,3000K,3500K
CRI	90
Construction	Extruded aluminum body with PC diffuser

REPLACEMENT PARTS

JB-0501 - 1" Slim Junction Box



WS-52127

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS-52127 27"	2700K	BN Brushed Nickel	17.2W	1077	768
	3000K	BN Brushed Nickel	17.2W	1113	815
	3500K	BN Brushed Nickel	17.2W	1140	815

Example: **WS-52127-35-BN**

For custom requests please contact customs@modernforms.com



Project:

Location:

Fixture Type:

Catalog Number:

AVAILABLE FINISHES:



Open Bar

WS-52137

PRODUCT DESCRIPTION

A window of opportunity. This intriguing bath bar features an open design that allows light to shine through. A CCT switch enables multiple color temperature options to customize the look and feel of the room. Utilizing state of the art ACLED driverless technology, the versatile luminaire comes with an optional 1" junction box that allows it to be installed to your precise position in the orientation of your choice.

FEATURES

- ACLED driverless technology
- 1" slim junction box included and can be ordered separately (model# JB-0501)
- Built in color temperature adjustability. Switch from 2700K/3000K/3500K
- Conversion plate included to accommodate 4" junction box
- Trimless spackle cover available for 4" square junction box recessed in drywall thicknesses of 1/2", 5/8", 1", and 1-1/4"; accessory not included and can be ordered separately (model# MKCP-3040-WT)
- Option to pre-select color temperature or adjust in the field

SPECIFICATIONS

Rated Life	54000 Hours
Standards	ETL, cETL,Damp Location Listed,Title 24 JA8: 2019 Compliant
Input	120 VAC,50/60Hz
Dimming	ELV: 100-10%,TRIAC: 100-5%
Mounting	Can be mounted on ceiling or wall in all orientations
Color Temp	3500K,3000K,2700K
CRI	90
Construction	Extruded aluminum body with PC diffuser

REPLACEMENT PARTS

JB-0501 - 1" Slim Junction Box



WS-52137

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS-52137 37"	2700K	BN Brushed Nickel	22.9W	1307	1045
	3000K	BN Brushed Nickel	22.9W	1369	1094
	3500K	BN Brushed Nickel	22.9W	1342	1112

Example: **WS-52137-35-BN**

For custom requests please contact customs@modernforms.com