




PD-30126


Project:

Location:

Fixture Type:

Catalog Number:

AVAILABLE FINISHES:



Luzerne

PD-30126

PRODUCT DESCRIPTION

Dramatically proportioned. Bundles of fluted glass cylinders are nested together creating a striking prismatic effect. A gleaming inner plate creates a mirrored effect, elegantly enhancing the delicate crystalline elements.

FEATURES

- Driver concealed within the canopy
- Extruded fluted glass
- Inner plate creates a mirrored effect
- Spin on canopy with minimal hardware
- Thin powered aircraft cables provide an ultra clean look for adjustable suspension height
- NEC CODE (314.24) requires that ceiling outlet boxes in the U.S. support up to 50 lbs.
- This fixture exceeds 50 lbs. and must be installed using a U.L. listed outlet box approved for up to 200 lbs. or supported independently of the outlet box
- Patented design

SPECIFICATIONS

Rated Life	50,000 Hours
Standards	ETL, cETL, Damp Location Listed
Input	120-277 VAC, 50/60Hz
Dimming	ELV, 0-10V, TRIAC
Color Temp	3000K
CRI	90
Construction	Welded steel body with clear extruded reeded glass

REPLACEMENT PARTS

RPL-GLA-30126-Z - Replacement Glass Z
 RPL-GLA-30126-R - Replacement Glass R
 RPL-GLA-30126-S - Replacement Glass S
 RPL-GLA-30126-T - Replacement Glass T
 RPL-GLA-30126-U - Replacement Glass U

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
PD-30126 26"	3000K	AB Aged Brass	121.3W	7000	6391
	3000K	BN Brushed Nickel	121.3W	7000	6391

Example: **PD-30126-BN**

For custom requests please contact customs@modernforms.com