## MODERN FORMS

## **Dimming Compatibility**

ID E2401042V0

**Product Family:** 

Sku Tested: PD-30126

**Related Models** 

Test Voltage: 120-277V

Control Type: ELV,TRIAC,MLV,0-10V

Test Notes: Refer to dimmer manufacturer's dimmer load rating for min and max fixture quantities per dimmer.

Manufacturer	Product	Model Number	Test Voltage (V)	Measured Dimming Range Low End	Comments
			Adaptive Phase D	Dimmers	
Control4	Adaptive	C4-APD120	120	0.2%	Noise at 1 meter away
Legrand	Adorne Touch (ELV)	ADTH700RMTUM1	120	2.0%	Flicker below 2%Noise at 1 meter away
Legrand	Adorne Touch (TRIAC)	ADTH700RMTUM1	120	13.0%	Not Recommended
Legrand	Radiant	RH703PTUW	120	8.0%	Noise at 1 meter away
Legrand	Adorne (ELV)	ADTP703TUW4	120	12.0%	
Legrand	Adorne (TRIAC)	ADTP703TUW4	120	7.0%	Not Recommended
Cooper	AL Series	AAL06	120	3.0%	Noise at 1 meter away
Control4	Adaptive	C4-APD277	277	1.0%	Noise at 1 meter away
		Rev	verse Phase Dim	mers (ELV)	
Lutron	Nova T	NTELV-600	120	7.0%	Noise at 1 meter away
Lutron	Diva	DVELV-300P	120	5.0%	Noise at 1 meter away
Lutron	Maestro	MAELV-600	120	1.0%	Noise at 1 meter away
Lutron	Skylark	SELV-300P	120	5.0%	Noise at 1 meter away
Leviton	Illumatech	IPE04-1LZ	120	5.0%	Noise at 1 meter away
Lutron	Maestro	RRD-6NA	120	1.0%	Noise at 1 meter away
Leviton	SureSlide	6615-P0W	120	12.0%	Noise at 1 meter away
Leviton	Decora	DSE06-10Z	120	4.0%	Noise at 1 meter away
Lutron	Caseta	PD-5NE	120	6.0%	Noise at 1 meter away
Lutron	Homeworks	HRD-5NE	120	53.0%	Flicker at high dimming level; Noise at 1 meter away
Lutron	Homeworks	HQRD-6NA	120	1.0%	Noise at 1 meter away
Leviton	Renoir II	AWSMT-EBW	120	0.2%	Noise at 1 meter away
Lutron	Grafik-Eye	GRX-3103-A-G	120	1.0%	Noise at 1 meter away
Leviton	Renoir II	AWSMT-EBW	277	1.0%	Noise at 1 meter away
Lutron	Grafik-Eye	GRX-3103-A-G	277	10.0%	Noise at 1 meter away
		Forv	vard Phase Dimn	ners (TRIAC)	
Lutron	Maestro	MACL-153M-WH	120	7.0%	Noise at 1 meter away
Lutron	Diva	DVCL-153P	120	2.0%	Noise at 1 meter away
Legrand	Adorne Paddle	ADPD453LW2	120	18.0%	Noise at 1 meter away
Lutron	Ariadni	AYCL-153PH	120	5.0%	Noise at 1 meter away

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects Modern Forms's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to Modern Forms, and therefore Modern Forms cannot ensure future compatibility. For any questions on this report, please contact Modern Forms Customer Service at 1-866-810-6615 or customerservice@modernforms.com.

## MODERN FORMS

Forward Phase Dimmers (TRIAC) Cont.								
Lutron	Skylark	SCL-153P-WH	120	2.0%	Noise at 1 meter away			
Lutron	Maestro	MA-600-WH	120	N/A	Dimmer not responsive			
Leviton	SureSlide	6674-POW	120	8.0%	Noise at 1 meter away			
Lutron	Caseta	PD-6WCL	120	0.1%	Noise at 1 meter away			
Legrand	Harmony	HCL453PW	120	6.0%	Noise at 1 meter away			
Legrand	Radiant	RHCL453PW	120	9.0%	Noise at 1 meter away			
0-10V Dimmers								
Lutron	Nova T	NTSTV	120	3.0%				
Leviton	Decora	IP710-LFZ	120	3.0%				
Control4	Adaptive	C4-TV120277	120	3.0%	Flicker below 3%			
Lutron	Diva	DVSTV	120	3.0%	Flicker below 3%			
Leviton	Renoir	AWSMT-7DW	120	5.0%				
Legrand	Radiant	RH4FBL3PW	120	3.0%	Flicker below 3%			
Lutron	Nova T	NTSTV	277	3.0%	Flicker below 3%			
Leviton	Decora	IP710-LFZ	277	3.0%	Flicker below 3%			
Control4	Adaptive	C4-TV120277	277	3.0%	Flicker below 3%			
Lutron	Diva	DVSTV	277	3.0%	Flicker below 3%			
Lutron	Diva	AWSMT-7DW	277	6.0%				
Legrand	Radiant	RH4FBL3PW	277	3.0%	Flicker below 3%			

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects Modern Forms's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to Modern Forms, and therefore Modern Forms cannot ensure future compatibility. For any questions on this report, please contact Modern Forms Customer Service at 1-866-810-6615 or customerservice@modernforms.com.