

# MODERN FORMS

## Dimming Compatibility

ID E1807072V0

**Product Family:** Mini Vogue

**Sku Tested:** WS-21712

**Related Model** -

**Numbers:**

**Test Voltage:** 120-277VAC

**Control Type:** ELV

**Test Notes:** Refer to dimmer manufacturer's dimmer load rating for min and max fixture quantities per dimmer.

Manufacturer	Product	Model Number	Test Voltage (V)	Measured Dimming Range	Comments
				Low End	
<b>Adaptive Phase Dimmers</b>					
Control4	Adaptive	C4-APD120	120	0.2%	
Legrand	Adorne Touch (ELV)	ADTH700RMTUM1	120	50.0%	Flicker below 50%
Legrand	Adorne Touch (TRIAC)	ADTH700RMTUM1	120	57.0%	Not Recommended
Legrand	Radiant	RH703PTUW	120	24.0%	Flicker below 24%
Legrand	Adorne (ELV)	ADTP703TUW4	120	10.0%	
Legrand	Adorne (TRIAC)	ADTP703TUW4	120	5.0%	Not Recommended
Cooper	AL Series	AAL06	120	9.0%	Flicker below 9%
Control4	Adaptive	C4-APD277	277	2.0%	
<b>Reverse Phase Dimmers (ELV)</b>					
Lutron	Nova T	NTELV-600	120	8.0%	
Lutron	Diva	DVELV-300P	120	4.0%	
Lutron	Maestro	MAELV-600	120	0.2%	
Lutron	Skylark	SELV-300P	120	4.0%	
Leviton	Illumatech	IPE04-1LZ	120	23.0%	
Lutron	Maestro	RRD-6NA	120	0.7%	Flicker below 0.7%
Leviton	SureSlide	6615-POW	120	14.0%	
Leviton	Decora	DSE06-10Z	120	3.0%	
Lutron	Caseta	PD-5NE	120	5.0%	
Lutron	Homeworks	HRD-5NE	120	N/A	Flashing at high dimming level
Leviton	Renoir II	AWSMT-EBW	120	0.2%	
Lutron	Grafik-Eye	GRX-3103-A-G	120	0.1%	
Leviton	Renoir II	AWSMT-EBW	277	0.2%	
Lutron	Grafik-Eye	GRX-3103-A-G	277	0.1%	
<b>Forward Phase Dimmers (TRIAC)</b>					
Lutron	Maestro	MAELV-153M-WH	120	53.0%	Not Recommended
Lutron	Diva	DVCL-153PD	120	45.0%	Not Recommended
Legrand	Adorne Paddle	ADPD453LW2	120	N/A	Not Recommended
Lutron	Ariadni	AYCL-153PH	120	39.0%	Not Recommended

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects Modern Forms's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to Modern Forms, and therefore Modern Forms cannot ensure future compatibility. For any questions on this report, please contact Modern Forms Customer Service at 1-866-810-6615 or customerservice@modernforms.com.

<b>Forward Phase Dimmers (TRIAC) Cont.</b>					
Lutron	Skylark	SCL-153P-WH	120	45.0%	Not Recommended
Lutron	Maestro	MA-600-WH	120	N/A	Not Recommended
Leviton	SureSlide	6674-POW	120	N/A	Not Recommended
Lutron	Caseta	PD-6WCL	120	49.0%	Not Recommended
Legrand	Harmony	HCL453PW	120	N/A	Not Recommended
Legrand	Radiant	RHCL453PW	120	N/A	Not Recommended

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects Modern Forms's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to Modern Forms, and therefore Modern Forms cannot ensure future compatibility. For any questions on this report, please contact Modern Forms Customer Service at 1-866-810-6615 or customerservice@modernforms.com.

# MODERN FORMS

## Dimming Compatibility

ID E1807069V0

**Product Family:** Mini Vogue

**Sku Tested:** WS-21718

**Related Model** -

**Numbers:**

**Test Voltage:** 120-277VAC

**Control Type:** ELV

**Test Notes:** Refer to dimmer manufacturer's dimmer load rating for min and max fixture quantities per dimmer.

Manufacturer	Product	Model Number	Test Voltage (V)	Measured Dimming Range	Comments
				Low End	
<b>Adaptive Phase Dimmers</b>					
Control4	Adaptive	C4-APD120	120	2.0%	
Legrand	Adorne Touch (ELV)	ADTH700RMTUM1	120	41.0%	Flicker below 41%
Legrand	Adorne Touch (TRIAC)	ADTH700RMTUM1	120	54.0%	Not Recommended
Legrand	Radiant	RH703PTUW	120	N/A	Dimmer not responsive
Legrand	Adorne (ELV)	ADTP703TUW4	120	18.0%	
Legrand	Adorne (TRIAC)	ADTP703TUW4	120	11.0%	Not Recommended
Cooper	AL Series	AAL06	120	3.0%	
Control4	Adaptive	C4-APD277	277	6.0%	
<b>Reverse Phase Dimmers (ELV)</b>					
Lutron	Nova T	NTELV-600	120	14.0%	
Lutron	Diva	DVELV-300P	120	10.0%	
Lutron	Maestro	MAELV-600	120	2.0%	
Lutron	Skylark	SELV-300P	120	10.0%	
Leviton	Illumatech	IPE04-1LZ	120	31.0%	
Lutron	Maestro	RRD-6NA	120	2.0%	
Leviton	SureSlide	6615-POW	120	21.0%	
Leviton	Decora	DSE06-10Z	120	7.0%	
Lutron	Caseta	PD-5NE	120	11.0%	
Lutron	Homeworks	HRD-5NE	120	99.0%	Flashing at high dimming level
Leviton	Renoir II	AWSMT-EBW	120	0.8%	
Lutron	Grafik-Eye	GRX-3103-A-G	120	1.0%	
Leviton	Renoir II	AWSMT-EBW	277	0.8%	
Lutron	Grafik-Eye	GRX-3103-A-G	277	1.0%	
<b>Forward Phase Dimmers (TRIAC)</b>					
Lutron	Maestro	MAELV-600	120	47.0%	Not Recommended
Lutron	Diva	DVCL-153PD	120	35.0%	Not Recommended
Legrand	Adorne Paddle	ADPD453LW2	120	N/A	Not Recommended
Lutron	Ariadni	AYCL-153PH	120	53.0%	Not Recommended

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects Modern Forms's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to Modern Forms, and therefore Modern Forms cannot ensure future compatibility. For any questions on this report, please contact Modern Forms Customer Service at 1-866-810-6615 or customerservice@modernforms.com.

<b>Forward Phase Dimmers (TRIAC) Cont.</b>					
Lutron	Skylark	SCL-153P-WH	120	47.0%	Not Recommended
Lutron	Maestro	MA-600-WH	120	N/A	Not Recommended
Leviton	SureSlide	6674-POW	120	N/A	Not Recommended
Lutron	Caseta	PD-6WCL	120	59.0%	Not Recommended
Legrand	Harmony	HCL453PW	120	23.0%	Not Recommended
Legrand	Radiant	RHCL453PW	120	17.0%	Not Recommended

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects Modern Forms's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to Modern Forms, and therefore Modern Forms cannot ensure future compatibility. For any questions on this report, please contact Modern Forms Customer Service at 1-866-810-6615 or customerservice@modernforms.com.

# MODERN FORMS

## Dimming Compatibility

ID E1807070V0

**Product Family:** Mini Vogue  
**SKU Tested:** WS-21724  
**Related Model Numbers:** -

**Test Voltage:** 120-277VAC  
**Control Type:** ELV  
**Test Notes:** Refer to dimmer manufacturer's dimmer load rating for min and max fixture quantities per dimmer.

Manufacturer	Product	Model Number	Test Voltage (V)	Measured Dimming Range	Comments
				Low End	
<b>Adaptive Phase Dimmers</b>					
Control4	Adaptive	C4-APD120	120	0.8%	
Legrand	Adorne Touch (ELV)	ADTH700RMTUM1	120	35.0%	Flicker below 35%
Legrand	Adorne Touch (TRIAC)	ADTH700RMTUM1	120	40.0%	Not Recommended
Legrand	Radiant	RH703PTUW	120	19.0%	
Legrand	Adorne (ELV)	ADTP703TUW4	120	12.0%	
Legrand	Adorne (TRIAC)	ADTP703TUW4	120	7.0%	Not Recommended
Cooper	AL Series	AAL06	120	13.0%	Flicker below 13%
Control4	Adaptive	C4-APD277	277	0.2%	
<b>Reverse Phase Dimmers (ELV)</b>					
Lutron	Nova T	NTELV-600	120	9.0%	
Lutron	Diva	DVELV-300P	120	5.0%	
Lutron	Maestro	MAELV-600	120	0.8%	
Lutron	Skylark	SELV-300P	120	5.0%	
Leviton	Illumatech	IPE04-1LZ	120	23.0%	
Lutron	Maestro	RRD-6NA	120	4.0%	Flicker below 4%
Leviton	SureSlide	6615-POW	120	15.0%	
Leviton	Decora	DSE06-10Z	120	4.0%	
Lutron	Caseta	PD-5NE	120	6.0%	
Lutron	Homeworks	HRD-5NE	120	N/A	Flashing at high dimming level
Leviton	Renoir II	AWSMT-EBW	120	0.1%	
Lutron	Grafik-Eye	GRX-3103-A-G	120	0.4%	
Leviton	Renoir II	AWSMT-EBW	277	0.1%	
Lutron	Grafik-Eye	GRX-3103-A-G	277	0.4%	
<b>Forward Phase Dimmers (TRIAC)</b>					
Lutron	Maestro	MAELV-153M-WH	120	63.0%	Not Recommended
Lutron	Diva	DVCL-153PD	120	52.0%	Not Recommended
Legrand	Adorne Paddle	ADPD453LW2	120	N/A	Not Recommended
Lutron	Ariadni	AYCL-153PH	120	46.0%	Not Recommended

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects Modern Forms's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to Modern Forms, and therefore Modern Forms cannot ensure future compatibility. For any questions on this report, please contact Modern Forms Customer Service at 1-866-810-6615 or customerservice@modernforms.com.

<b>Forward Phase Dimmers (TRIAC) Cont.</b>					
Lutron	Skylark	SCL-153P-WH	120	47.0%	Not Recommended
Lutron	Maestro	MA-600-WH	120	N/A	Not Recommended
Leviton	SureSlide	6674-POW	120	N/A	Not Recommended
Lutron	Caseta	PD-6WCL	120	54.0%	Not Recommended
Legrand	Harmony	HCL453PW	120	N/A	Not Recommended
Legrand	Radiant	RHCL453PW	120	N/A	Not Recommended

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects Modern Forms's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to Modern Forms, and therefore Modern Forms cannot ensure future compatibility. For any questions on this report, please contact Modern Forms Customer Service at 1-866-810-6615 or customerservice@modernforms.com.

**Product Family:** Mini Vogue

**SKU Tested:** WS-21736

**Related Model** -

**Numbers:**

**Test Voltage:** 120-277VAC

**Control Type:** ELV

**Test Notes:** Refer to dimmer manufacturer's dimmer load rating for min and max fixture quantities per dimmer.

Manufacturer	Product	Model Number	Test Voltage (V)	Measured Dimming Range	Comments
				Low End	
<b>Adaptive Phase Dimmers</b>					
Control4	Adaptive	C4-APD120	120	0.1%	
Legrand	Adorne Touch (ELV)	ADTH700RMTUM1	120	31.0%	Flicker below 31%
Legrand	Adorne Touch (TRIAC)	ADTH700RMTUM1	120	40.0%	Not Recommended
Legrand	Radiant	RH703PTUW	120	14.0%	
Legrand	Adorne (ELV)	ADTP703TUW4	120	8.0%	
Legrand	Adorne (TRIAC)	ADTP703TUW4	120	3.0%	Not Recommended
Cooper	AL Series	AAL06	120	22.0%	Flicker below 22%
Control4	Adaptive	C4-APD277	277	1.0%	
<b>Reverse Phase Dimmers (ELV)</b>					
Lutron	Nova T	NTELV-600	120	5.0%	
Lutron	Diva	DVELV-300P	120	2.0%	
Lutron	Maestro	MAELV-600	120	0.1%	
Lutron	Skylark	SELV-300P	120	2.0%	
Leviton	Illuminate	IPE04-1LZ	120	17.0%	
Lutron	Maestro	RRD-6NA	120	0.0%	
Leviton	SureSlide	6615-POW	120	10.0%	
Leviton	Decora	DSE06-10Z	120	2.0%	
Lutron	Caseta	PD-5NE	120	4.0%	
Lutron	Homeworks	HRD-5NE	120	N/A	Flashing at high dimming level
Leviton	Renoir II	AWSMT-EBW	120	0.6%	
Lutron	Grafik-Eye	GRX-3103-A-G	120	0.2%	
Leviton	Renoir II	AWSMT-EBW	277	0.6%	
Lutron	Grafik-Eye	GRX-3103-A-G	277	0.2%	
<b>Forward Phase Dimmers (TRIAC)</b>					
Lutron	Maestro	MAELV-153M-WH	120	56.0%	Not Recommended
Lutron	Diva	DVCL-153PD	120	24.0%	Not Recommended
Legrand	Adorne Paddle	ADPD453LW2	120	N/A	Not Recommended
Lutron	Ariadni	AYCL-153PH	120	39.0%	Not Recommended

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects WAC's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to WAC Lighting, and therefore WAC Lighting cannot ensure future compatibility. For any questions on this report, please contact WAC Lighting Customer Service at 1-800-526-2588 or sales@wacighting.com.

<b>Forward Phase Dimmers (TRIAC) Cont.</b>					
Lutron	Skylark	SCL-153P-WH	120	41.0%	Not Recommended
Lutron	Maestro	MA-600-WH	120	N/A	Not Recommended
Leviton	SureSlide	6674-POW	120	N/A	Not Recommended
Lutron	Caseta	PD-6WCL	120	45.0%	Not Recommended
Legrand	Harmony	HCL453PW	120	11.0%	Not Recommended
Legrand	Radiant	RHCL453PW	120	12.0%	Not Recommended

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects WAC's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to WAC Lighting, and therefore WAC Lighting cannot ensure future compatibility. For any questions on this report, please contact WAC Lighting Customer Service at 1-800-526-2588 or sales@wacighting.com.