

MODERN FORMS

Dimming Compatibility

ID E1805086V0

Product: LEDGE
Family:
Sku Tested: WS-W1408
Related Model:

Test Voltage: 120VAC

Control Type: ELV

Test Notes: Refer to dimmer manufacturer's dimmer load rating for min and max fixture quantities per dimmer.

Manufacturer	Product	Model Number	Test Voltage (V)	Measured Dimming Range	Comments
				Low End	
Adaptive Phase Dimmers					
Control4	Adaptive	C4-APD120	120	5.0%	
Legrand	Adorne Touch (ELV)	ADTH700RMTUM1	120	16.0%	Flicker below 16%
Legrand	Adorne Touch (TRIAC)	ADTH700RMTUM1	120	16.0%	Flicker below 16%
Legrand	Radiant	RH703PTUW	120	10.0%	Flicker below 10%
Legrand	Adorne (ELV)	ADTP703TUW4	120	5.0%	
Legrand	Adorne (TRIAC)	ADTP703TUW4	120	5.0%	
Cooper	AL Series	AAL06	120	N/A	Flashing at high dimming level
Reverse Phase Dimmers (ELV)					
Lutron	Nova T	NTELV-600	120	5.0%	
Lutron	Diva	DVELV-300P	120	5.0%	
Lutron	Maestro	MAELV-600	120	6.0%	
Lutron	Skylark	SELV-300P	120	5.0%	
Leviton	Illuminatech	IPE04-1LZ	120	11.0%	
Lutron	Maestro	RRD-6NA	120	5.0%	
Leviton	SureSlide	6615-POW	120	8.0%	
Leviton	Decora	DSE06-10Z	120	5.0%	
Lutron	Caseta	PD-5NE	120	5.0%	
Lutron	Homeworks	HRD-5NE	120	5.0%	
Leviton	Renoir II	AWSMT-EBW	120	5.0%	
Lutron	Grafik-Eye	GRX-3103-A-G	120	5.0%	
Forward Phase Dimmers (TRIAC)					
Lutron	Maestro	MACL-153M-WH	120	5.0%	
Lutron	Diva	DVCL-153PD	120	5.0%	
Legrand	Adorne Paddle	ADPD453LW2	120	N/A	Flashing at high dimming level
Lutron	Ariadni	AYCL-153PH	120	7.0%	
Lutron	Skylark	SCL-153P-WH	120	5.0%	
Lutron	Maestro	MA-600-WH	120	N/A	
Leviton	SureSlide	6674-POW	120	6.0%	

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects WAC's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to WAC Lighting, and therefore WAC Lighting cannot ensure future compatibility. For any questions on this report, please contact WAC Lighting Customer Service at 1-800-526-2588 or sales@waclighting.com.

Forward Phase Dimmers (TRIAC) Cont.					
Lutron	Caseta	PD-6WCL	120	17.0%	Flicker below 17%
Legrand	Harmony	HCL453PW	120	5.0%	
Legrand	Radiant	RHCL453PW	120	6.0%	Flashing at low dimming level

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects WAC's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to WAC Lighting, and therefore WAC Lighting cannot ensure future compatibility. For any questions on this report, please contact WAC Lighting Customer Service at 1-800-526-2588 or sales@wacighting.com.

MODERN FORMS

Dimming Compatibility

ID E1710258V0

Product Family: LEDGE

Sku Tested: WS-W1412

Related Models

Test Voltage: 120V

Control Type: ELV

Test Notes: Refer to dimmer manufacturer's dimmer load rating for min and max fixture quantities per dimmer.

Manufacturer	Product	Model Number	Test Voltage (V)	Measured Dimming Range	Comments
				Low End	
Adaptive Phase Dimmers					
Control4	Adaptive	C4-APD120	120	5.0%	
Legrand	Adorne Touch (ELV)	ADTH700RMTUM1	120	5.0%	
Legrand	Adorne Touch (TRIAC)	ADTH700RMTUM1	120	4.0%	Not Recommended
Legrand	Radiant	RH703PTUW	120	19.0%	Flicker below 19%
Legrand	Adorne (ELV)	ADTP703TUW4	120	6.0%	
Legrand	Adorne (TRIAC)	ADTP703TUW4	120	6.0%	Not Recommended
Cooper	AL Series	AAL06	120	17.0%	Flicker below 17%
Reverse Phase Dimmers (ELV)					
Lutron	Nova T	NTELV-600	120	5.0%	
Lutron	Diva	DVELV-300P	120	5.0%	
Lutron	Maestro	MAELV-600	120	5.0%	
Lutron	Skylark	SELV-300P	120	5.0%	
Leviton	Illumatech	IPE04-1LZ	120	11.0%	
Lutron	Maestro	RRD-6NA	120	5.0%	
Leviton	SureSlide	6615-POW	120	8.0%	
Leviton	Decora	DSE06-10Z	120	5.0%	
Lutron	Caseta	PD-5NE	120	5.0%	
Lutron	Homeworks	HRD-5NE	120	5.0%	
Lutron	Homeworks	HQRD-6NA	120	N/A	
Leviton	Renoir II	AWSMT-EBW	120	5.0%	
Lutron	Grafik-Eye	GRX-3103-A-G	120	5.0%	
Forward Phase Dimmers (TRIAC)					
Lutron	Maestro	MACL-153M-WH	120	5.0%	Not Recommended
Lutron	Diva	DVCL-153P	120	5.0%	Not Recommended
Legrand	Adorne Paddle	ADPD453LW2	120	10.0%	Not Recommended
Lutron	Ariadni	AYCL-153PH	120	7.0%	Not Recommended
Lutron	Skylark	SCL-153P-WH	120	5.0%	Not Recommended
Lutron	Maestro	MA-600-WH	120	N/A	Not Recommended
Leviton	SureSlide	6674-POW	120	9.0%	Not Recommended
Lutron	Caseta	PD-6WCL	120	17.0%	Not Recommended
Legrand	Harmony	HCL453PW	120	5.0%	Not Recommended
Legrand	Radiant	RHCL453PW	120	4.0%	Not Recommended

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects Modern Forms's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to Modern Forms, and therefore Modern Forms cannot ensure future compatibility. For any questions on this report, please contact Modern Forms Customer Service at 1-866-810-6615 or customerservice@modernforms.com.

MODERN FORMS

Dimming Compatibility

ID E1811087V0

Product Family: LEDGE
Sku Tested: WS-W1414
Related Model:

Test Voltage: 120V
Control Type: ELV

Test Notes: Refer to dimmer manufacturer's dimmer load rating for min and max fixture quantities per dimmer.

Manufacturer	Product	Model Number	Test Voltage (V)	Measured Dimming Range	Comments
				Low End	
Adaptive Phase Dimmers					
Control4	Adaptive	C4-APD120	120	7.0%	
Legrand	Adorne Touch (ELV)	ADTH700RMTUM1	120	7.0%	
Legrand	Adorne Touch (TRIAC)	ADTH700RMTUM1	120	7.0%	
Legrand	Radiant	RH703PTUW	120	7.0%	
Legrand	Adorne (ELV)	ADTP703TUW4	120	7.0%	
Legrand	Adorne (TRIAC)	ADTP703TUW4	120	7.0%	
Cooper	AL Series	AAL06	120	N/A	
Reverse Phase Dimmers (ELV)					
Lutron	Nova T	NTELV-600	120	7.0%	
Lutron	Diva	DVELV-300P	120	7.0%	
Lutron	Maestro	MAELV-600	120	8.0%	
Lutron	Skylark	SELV-300P	120	8.0%	
Leviton	Illumatech	IPE04-1LZ	120	11.0%	
Lutron	Maestro	RRD-6NA	120	8.0%	
Leviton	SureSlide	6615-POW	120	8.0%	
Leviton	Decora	DSE06-10Z	120	8.0%	
Lutron	Caseta	PD-5NE	120	8.0%	
Lutron	Homeworks	HRD-5NE	120	N/A	Flashing at high dimming level
Leviton	Renoir II	AWSMT-EBW	120	10.0%	
Lutron	Grafik-Eye	GRX-3103-A-G	120	9.0%	
Forward Phase Dimmers (TRIAC)					
Lutron	Maestro	MACL-153M-WH	120	32.0%	Flashing at low dimming level
Lutron	Diva	DVCL-153PD	120	43.0%	Flashing at low dimming level
Legrand	Adorne Paddle	ADPD453LW2	120	27.0%	Flashing at high dimming level
Lutron	Ariadni	AYCL-153PH	120	44.0%	Flashing at high dimming level
Lutron	Skylark	SCL-153P-WH	120	44.0%	Flashing at high dimming level
Lutron	Maestro	MA-600-WH	120	25.0%	Flashing at low dimming level
Leviton	SureSlide	6674-POW	120	26.0%	Flashing at low dimming level

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects WAC's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to WAC Lighting, and therefore WAC Lighting cannot ensure future compatibility. For any questions on this report, please contact WAC Lighting

Customer Service at 1-800-526-2588 or sales@wacighting.com.

Forward Phase Dimmers (TRIAC) Cont.					
Lutron	Caseta	PD-6WCL	120	48.0%	Flashing at high dimming level
Legrand	Harmony	HCL453PW	120	43.0%	Flashing at high dimming level
Legrand	Radiant	RHCL453PW	120	23.0%	Flashing at low dimming level

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects WAC's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to WAC Lighting, and therefore WAC Lighting cannot ensure future compatibility. For any questions on this report, please contact WAC Lighting Customer Service at 1-800-526-2588 or sales@wacighting.com.

MODERN FORMS

Dimming Compatibility

ID E1710258V0

Product Family: LEDGE
Sku Tested: WS-W1420
Related Model:

Test Voltage: 120VAC

Control Type: ELV

Test Notes: Refer to dimmer manufacturer's dimmer load rating for min and max fixture quantities per dimmer.

Manufacturer	Product	Model Number	Test Voltage (V)	Measured Dimming Range	Comments
				Low End	
Adaptive Phase Dimmers					
Control4	Adaptive	C4-APD120	120	5.0%	
Legrand	Adorne Touch (ELV)	ADTH700RMTUM1	120	5.0%	
Legrand	Adorne Touch (TRIAC)	ADTH700RMTUM1	120	5.0%	
Legrand	Radiant	RH703PTUW	120	19.0%	Flicker below 19%
Legrand	Adorne (ELV)	ADTP703TUW4	120	6.0%	
Legrand	Adorne (TRIAC)	ADTP703TUW4	120	6.0%	
Cooper	AL Series	AAL06	120	17.0%	Flicker below 17%
Reverse Phase Dimmers (ELV)					
Lutron	Nova T	NTELV-600	120	5.0%	
Lutron	Diva	DVELV-300P	120	5.0%	
Lutron	Maestro	MAELV-600	120	5.0%	
Lutron	Skylark	SELV-300P	120	5.0%	
Leviton	Illumatech	IPE04-1LZ	120	11.0%	
Lutron	Maestro	RRD-6NA	120	5.0%	
Leviton	SureSlide	6615-POW	120	8.0%	
Leviton	Decora	DSE06-10Z	120	5.0%	
Lutron	Caseta	PD-5NE	120	5.0%	
Lutron	Homeworks	HRD-5NE	120	5.0%	
Leviton	Renoir II	AWSMT-EBW	120	5.0%	
Lutron	Grafik-Eye	GRX-3103-A-G	120	5.0%	
Forward Phase Dimmers (TRIAC)					
Lutron	Maestro	MACL-153M-WH	120	5.0%	
Lutron	Diva	DVCL-153PD	120	5.0%	
Legrand	Adorne Paddle	ADPD453LW2	120	10.0%	Flashing at low dimming level
Lutron	Ariadni	AYCL-153PH	120	7.0%	
Lutron	Skylark	SCL-153P-WH	120	5.0%	Flicker below 5%
Lutron	Maestro	MA-600-WH	120	N/A	Dimmer not responsive
Leviton	SureSlide	6674-POW	120	9.0%	Flicker below 9%

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects WAC's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to WAC Lighting, and therefore WAC Lighting cannot ensure future compatibility. For any questions on this report, please contact WAC Lighting Customer Service at 1-800-526-2588 or sales@wacighting.com.

Forward Phase Dimmers (TRIAC) Cont.					
Lutron	Caseta	PD-6WCL	120	17.0%	Flicker below 17%
Legrand	Harmony	HCL453PW	120	5.0%	
Legrand	Radiant	RHCL453PW	120	4.0%	Flicker below 4%

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects WAC's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to WAC Lighting, and therefore WAC Lighting cannot ensure future compatibility. For any questions on this report, please contact WAC Lighting Customer Service at 1-800-526-2588 or sales@wacighting.com.