

# MODERN FORMS

## DIMMING COMPATIBILITY

ID E1811006V0

**Product Family:**

**Sku Tested:** WS-W37916 & WS-W37922

**Related Models**

**Test Voltage:** 120V

**Control Type:**

**Test Notes:** Refer to dimmer manufacturer's dimmer load rating for min and max fixture quantities per dimmer.

Manufacturer	Product	Model Number	Test Voltage (V)	Measured Dimming Range	Comments
				Low End	
<b>Adaptive Phase Dimmers</b>					
Control4	Adaptive	C4-APD120	120	5.0%	
Legrand	Adorne Touch (ELV)	ADTH700RMTUM1	120	55.0%	Flashing at high dimming level
Legrand	Adorne Touch (TRIAC)	ADTH700RMTUM1	120	71.0%	Not Recommended
Legrand	Radiant	RH703PTUW	120	7.0%	
Legrand	Adorne (ELV)	ADTP703TUU4	120	4.0%	
Legrand	Adorne (TRIAC)	ADTP703TUU4	120	5.0%	Not Recommended
Cooper	AL Series	AAL06	120	N/A	Flashing at high dimming level
<b>Reverse Phase Dimmers (ELV)</b>					
Lutron	Nova T	NTELV-600	120	5.0%	
Lutron	Diva	DVELV-300P	120	5.0%	
Lutron	Maestro	MAELV-600	120	8.0%	Flicker below 8%
Lutron	Skylark	SELV-300P	120	5.0%	
Leviton	Illumatech	IPE04-1LZ	120	10.0%	
Lutron	Maestro	RRD-6NA	120	10.0%	Flicker below 10%
Leviton	SureSlide	6615-POW	120	6.0%	
Leviton	Decora	DSE06-10Z	120	5.0%	
Lutron	Caseta	PD-5NE	120	8.0%	Flicker below 8%
Lutron	Homeworks	HRD-5NE	120	N/A	Flashing at high dimming level
Leviton	Renoir II	AWSMT-EBW	120	5.0%	
Lutron	Grafik-Eye	GRX-3103-A-G	120	9.0%	Flicker below 9%
<b>Forward Phase Dimmers (TRIAC)</b>					
Lutron	Maestro	MACL-153M-WH	120	9.0%	Flicker below 9%
Lutron	Diva	DVCL-153P	120	25.0%	Flicker below 25%
Legrand	Adorne Paddle	ADPD453LW2	120	14.0%	Flicker below 14%
Lutron	Ariadni	AYCL-153PH	120	10.0%	Flicker below 10%
Lutron	Skylark	SCL-153P-WH	120	10.0%	Flicker below 10%
Lutron	Maestro	MA-600-WH	120	N/A	Dimmer not responsive
Leviton	SureSlide	6674-POW	120	12.0%	Flicker below 12%
Lutron	Caseta	PD-6WCL	120	14.0%	Flicker below 14%
Legrand	Harmony	HCL453PW	120	8.0%	Flicker below 8%
Legrand	Radiant	RHCL453PW	120	7.0%	Flicker below 7%

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects Modern Forms's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to Modern Forms, and therefore Modern Forms cannot ensure future compatibility. For any questions on this report, please contact Modern Forms Customer Service at 1-866-810-6615 or customerservice@modernforms.com.