

# MODERN FORMS

## Dimming Compatibility

ID E1905037V0

**Product Family:** Cascade

**Skus Tested:** PD-41703R

**Related Models** PD-41705L-\*; PD-41723L-\*

**Test Voltage:** 120-277V

**Control Type:** ELV

**Test Notes:** Refer to dimmer manufacturer's dimmer load rating for min and max fixture quantities per dimmer.

Manufacturer	Product	Model Number	Test Voltage (V)	Measured Dimming Range	Comments
				Low End	
<b>Adaptive Phase Dimmers</b>					
Control4	Adaptive	C4-APD120	120	0.7%	Flicker below 0.7%
Legrand	Adorne Touch (ELV)	ADTH700RMTUM1	120	39.0%	Flicker below 39%
Legrand	Adorne Touch (TRIAC)	ADTH700RMTUM1	120	39.0%	Not Recommended
Legrand	Radiant	RH703PTUW	120	11.0%	Flicker below 11%
Legrand	Adorne (ELV)	ADTP703TUW4	120	11.0%	
Legrand	Adorne (TRIAC)	ADTP703TUW4	120	14.0%	Not Recommended
Cooper	AL Series	AAL06	120	35.0%	Flicker below 35%
Control4	Adaptive	C4-APD277	277	0.0%	
<b>Reverse Phase Dimmers (ELV)</b>					
Lutron	Nova T	NTELV-600	120	7.0%	
Lutron	Diva	DVELV-300P	120	3.0%	
Lutron	Maestro	MAELV-600	120	0.9%	
Lutron	Skylark	SELV-300P	120	2.0%	
Leviton	Illumatech	IPE04-1LZ	120	23.0%	
Lutron	Maestro	RRD-6NA	120	0.1%	
Leviton	SureSlide	6615-POW	120	13.0%	
Leviton	Decora	DSE06-10Z	120	1.0%	
Lutron	Caseta	PD-5NE	120	4.0%	
Lutron	Homeworks	HRD-5NE	120	N/A	Flashing at all dimming levels
Lutron	Homeworks	HQRD-6NA	120	1.0%	
Leviton	Renoir II	AWSMT-EBW	120	0.1%	
Lutron	Grafik-Eye	GRX-3103-A-G	120	11.0%	Flicker below 11%
Leviton	Renoir II	AWSMT-EBW	277	2.0%	
Lutron	Grafik-Eye	GRX-3103-A-G	277	9.0%	Flicker below 11%
<b>Forward Phase Dimmers (TRIAC)</b>					
Lutron	Maestro	MACL-153M-WH	120	15.0%	Not Recommended
Lutron	Diva	DVCL-153P	120	35.0%	Not Recommended
Legrand	Adorne Paddle	ADPD453LW2	120	N/A	Not Recommended
Lutron	Ariadni	AYCL-153PH	120	31.0%	Not Recommended

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects Modern Forms's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to Modern Forms, and therefore Modern Forms cannot ensure future compatibility. For any questions on this report, please contact Modern Forms Customer Service at 1-866-810-6615 or customerservice@modernforms.com.

# MODERN FORMS

Forward Phase Dimmers (TRIAC) Cont.					
Lutron	Skylark	SCL-153P-WH	120	35.0%	Not Recommended
Lutron	Maestro	MA-600-WH	120	N/A	Not Recommended
Leviton	SureSlide	6674-POW	120	N/A	Not Recommended
Lutron	Caseta	PD-6WCL	120	20.0%	Not Recommended
Legrand	Harmony	HCL453PW	120	N/A	Not Recommended
Legrand	Radiant	RHCL453PW	120	N/A	Not Recommended

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects Modern Forms's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to Modern Forms, and therefore Modern Forms cannot ensure future compatibility. For any questions on this report, please contact Modern Forms Customer Service at 1-866-810-6615 or [customerservice@modernforms.com](mailto:customerservice@modernforms.com).