

MODERN FORMS

Dimming Compatibility

ID E1805034V0

Product Family: ARGO

SKU Tested: FM-4207

Related Models: -

Test Voltage: 120V

Control Type: ELV, TRIAC

Test Notes: Refer to dimmer manufacturer's dimmer load rating for min and max fixture quantities per dimmer.

| Manufacturer | Product | Model Number | Test Voltage (V) | Measured Dimming Range | Comments |
|--------------------------------------|----------------------|---------------|------------------|------------------------|--------------------------------|
| | | | | Low End | |
| Adaptive Phase Dimmers | | | | | |
| Control4 | Adaptive | C4-APD120 | 120 | 2.0% | |
| Legrand | Adorne Touch (ELV) | ADTH700RMTUM1 | 120 | 0.2% | Flashing at low dimming level |
| Legrand | Adorne Touch (TRIAC) | ADTH700RMTUM1 | 120 | 1.0% | Flashing at low dimming level |
| Legrand | Radiant | RH703PTUW | 120 | 7.0% | |
| Legrand | Adorne (ELV) | ADTP703TUW4 | 120 | 7.0% | |
| Legrand | Adorne (TRIAC) | ADTP703TUW4 | 120 | 5.0% | |
| Cooper | AL Series | AAL06 | 120 | 19.0% | Flicker below 19% |
| Reverse Phase Dimmers (ELV) | | | | | |
| Lutron | Nova T | NTELV-600 | 120 | 7.0% | |
| Lutron | Diva | DVELV-300P | 120 | 2.0% | |
| Lutron | Maestro | MAELV-600 | 120 | 1.0% | |
| Lutron | Skylark | SELV-300P | 120 | 2.0% | |
| Leviton | Illumatech | IPE04-1LZ | 120 | 17.0% | |
| Lutron | Maestro | RRD-6NA | 120 | 1.0% | |
| Leviton | SureSlide | 6615-POW | 120 | 12.0% | |
| Leviton | Decora | DSE06-10Z | 120 | 3.0% | |
| Lutron | Caseta | PD-5NE | 120 | 5.0% | |
| Lutron | Homeworks | HRD-5NE | 120 | N/A | Flashing at high dimming level |
| Leviton | Renoir II | AWSMT-EBW | 120 | 2.0% | |
| Lutron | Grafik-Eye | GRX-3103-A-G | 120 | 2.0% | |
| Forward Phase Dimmers (TRIAC) | | | | | |
| Lutron | Maestro | MAELV-153M-WH | 120 | 4.0% | |
| Lutron | Diva | DVCL-153PD | 120 | 5.0% | |
| Legrand | Adorne Paddle | ADPD453LW2 | 120 | 11.0% | |
| Lutron | Ariadni | AYCL-153PH | 120 | 12.0% | |
| Lutron | Skylark | SCL-153P-WH | 120 | N/A | Flashing at high dimming level |
| Lutron | Maestro | MA-600-WH | 120 | 6.0% | |
| Leviton | SureSlide | 6674-POW | 120 | 4.0% | |
| Lutron | Caseta | PD-6WCL | 120 | 5.0% | |
| Legrand | Harmony | HCL453PW | 120 | 12.0% | |
| Legrand | Radiant | RHCL453PW | 120 | 11.0% | |

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects Modern Forms's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to Modern Forms, and therefore Modern Forms cannot ensure future compatibility. For any questions on this report, please contact Modern Forms Customer Service at 1-866-810-6615 or customerservice@modernforms.com.

MODERN FORMS

Dimming Compatibility

ID E1805035V0

Product Family: ARGO
SKU Tested: FM-4211
Related Models: -

Test Voltage: 120V
Control Type: ELV, TRIAC

Test Notes: Refer to dimmer manufacturer's dimmer load rating for min and max fixture quantities per dimmer.

| Manufacturer | Product | Model Number | Test Voltage (V) | Measured Dimming Range | Comments |
|--------------------------------------|----------------------|---------------|------------------|------------------------|--------------------------------|
| | | | | Low End | |
| Adaptive Phase Dimmers | | | | | |
| Control4 | Adaptive | C4-APD120 | 120 | 12.0% | Flicker below 12% |
| Legrand | Adorne Touch (ELV) | ADTH700RMTUM1 | 120 | 9.0% | |
| Legrand | Adorne Touch (TRIAC) | ADTH700RMTUM1 | 120 | 4.0% | |
| Legrand | Radiant | RH703PTUW | 120 | 9.0% | |
| Legrand | Adorne (ELV) | ADTP703TUUW4 | 120 | 9.0% | |
| Legrand | Adorne (TRIAC) | ADTP703TUUW4 | 120 | 5.0% | |
| Cooper | AL Series | AAL06 | 120 | 2.0% | |
| Reverse Phase Dimmers (ELV) | | | | | |
| Lutron | Nova T | NTELV-600 | 120 | 18.0% | Flicker below 18% |
| Lutron | Diva | DVELV-300P | 120 | 19.0% | Flicker below 19% |
| Lutron | Maestro | MAELV-600 | 120 | 17.0% | Flicker below 17% |
| Lutron | Skylark | SELV-300P | 120 | 18.0% | Flicker below 18% |
| Leviton | Illuminatech | IPE04-1LZ | 120 | 20.0% | |
| Lutron | Maestro | RRD-6NA | 120 | 19.0% | Flicker below 19% |
| Leviton | SureSlide | 6615-POW | 120 | 15.0% | Flicker below 15% |
| Leviton | Decora | DSE06-10Z | 120 | 19.0% | Flicker below 19% |
| Lutron | Caseta | PD-5NE | 120 | 18.0% | Flicker below 18% |
| Lutron | Homeworks | HRD-5NE | 120 | N/A | Flashing at all dimming levels |
| Leviton | Renoir II | AWSMT-EBW | 120 | 0.5% | |
| Lutron | Grafik-Eye | GRX-3103-A-G | 120 | 27.0% | Flicker below 27% |
| Forward Phase Dimmers (TRIAC) | | | | | |
| Lutron | Maestro | MAEL-153M-WH | 120 | 5.0% | |
| Lutron | Diva | DVCL-153PD | 120 | 5.0% | |
| Legrand | Adorne Paddle | ADPD453LW2 | 120 | 14.0% | |
| Lutron | Ariadni | AYCL-153PH | 120 | 14.0% | |
| Lutron | Skylark | SCL-153P-WH | 120 | 5.0% | |
| Lutron | Maestro | MA-600-WH | 120 | N/A | Flashing at high dimming level |
| Leviton | SureSlide | 6674-POW | 120 | 5.0% | |
| Lutron | Caseta | PD-6WCL | 120 | 5.0% | |
| Legrand | Harmony | HCL453PW | 120 | 14.0% | |
| Legrand | Radiant | RHCL453PW | 120 | 13.0% | |

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects Modern Forms's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to Modern Forms, and therefore Modern Forms cannot ensure future compatibility. For any questions on this report, please contact Modern Forms Customer Service at 1-866-810-6615 or customerservice@modernforms.com.

MODERN FORMS

Dimming Compatibility

ID E1805036V0

Product Family: ARGO
SKU Tested: FM-4215
Related Models: -

Test Voltage: 120V
Control Type: ELV, TRIAC

Test Notes: Refer to dimmer manufacturer's dimmer load rating for min and max fixture quantities per dimmer.

| Manufacturer | Product | Model Number | Test Voltage (V) | Measured Dimming Range | Comments |
|--------------------------------------|----------------------|---------------|------------------|------------------------|--------------------------------|
| | | | | Low End | |
| Adaptive Phase Dimmers | | | | | |
| Control4 | Adaptive | C4-APD120 | 120 | 1.0% | |
| Legrand | Adorne Touch (ELV) | ADTH700RMTUM1 | 120 | 25.0% | Flicker below 25% |
| Legrand | Adorne Touch (TRIAC) | ADTH700RMTUM1 | 120 | #VALUE! | |
| Legrand | Radiant | RH703PTUW | 120 | 15.0% | |
| Legrand | Adorne (ELV) | ADTP703TUW4 | 120 | 38.0% | |
| Legrand | Adorne (TRIAC) | ADTP703TUW4 | 120 | #VALUE! | |
| Cooper | AL Series | AAL06 | 120 | 3.0% | |
| Reverse Phase Dimmers (ELV) | | | | | |
| Lutron | Nova T | NTELV-600 | 120 | 12.0% | |
| Lutron | Diva | DVELV-300P | 120 | 2.0% | |
| Lutron | Maestro | MAELV-600 | 120 | 0.9% | |
| Lutron | Skylark | SELV-300P | 120 | 27.0% | Flicker below 27% |
| Leviton | Illumatech | IPE04-1LZ | 120 | 18.0% | |
| Lutron | Maestro | RRD-6NA | 120 | 0.8% | |
| Leviton | SureSlide | 6615-POW | 120 | 14.0% | |
| Leviton | Decora | DSE06-10Z | 120 | 11.0% | Flicker below 11% |
| Lutron | Caseta | PD-5NE | 120 | 5.0% | |
| Lutron | Homeworks | HRD-5NE | 120 | N/A | Flashing at all dimming levels |
| Leviton | Renoir II | AWSMT-EBW | 120 | 13.0% | Flicker below 13% |
| Lutron | Grafik-Eye | GRX-3103-A-G | 120 | 18.0% | Flicker below 18% |
| Forward Phase Dimmers (TRIAC) | | | | | |
| Lutron | Maestro | MAELV-153M-WH | 120 | 5.0% | |
| Lutron | Diva | DVCL-153PD | 120 | 5.0% | |
| Legrand | Adorne Paddle | ADPD453LW2 | 120 | 13.0% | |
| Lutron | Ariadni | AYCL-153PH | 120 | 13.0% | |
| Lutron | Skylark | SCL-153P-WH | 120 | 47.0% | Flashing at high dimming level |
| Lutron | Maestro | MA-600-WH | 120 | 5.0% | |
| Leviton | SureSlide | 6674-POW | 120 | 5.0% | |
| Lutron | Caseta | PD-6WCL | 120 | 5.0% | |
| Legrand | Harmony | HCL453PW | 120 | 13.0% | |
| Legrand | Radiant | RHCL453PW | 120 | 12.0% | |

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects Modern Forms's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to Modern Forms, and therefore Modern Forms cannot ensure future compatibility. For any questions on this report, please contact Modern Forms Customer Service at 1-866-810-6615 or customerservice@modernforms.com.

MODERN FORMS

Dimming Compatibility

ID E1809076V0

Product Family: Argo

Sku Tested: FM-4219-BN

Related Models -

Test Voltage: 120V

Control Type: ELV/TRIAC

Test Notes: Refer to dimmer manufacturer's dimmer load rating for min and max fixture quantities per dimmer.

| Manufacturer | Product | Model Number | Test Voltage (V) | Measured Dimming Range | Comments |
|--------------------------------------|----------------------|---------------|------------------|------------------------|--------------------------------|
| | | | | Low End | |
| Adaptive Phase Dimmers | | | | | |
| Control4 | Adaptive | C4-APD120 | 120 | 2.0% | |
| Legrand | Adorne Touch (ELV) | ADTH700RMTUM1 | 120 | 52.0% | Flicker below 52% |
| Legrand | Adorne Touch (TRIAC) | ADTH700RMTUM1 | 120 | 2.0% | Not Recommended |
| Legrand | Radiant | RH703PTUW | 120 | N/A | Dimmer not responsive |
| Legrand | Adorne (ELV) | ADTP703TUW4 | 120 | 50.0% | |
| Legrand | Adorne (TRIAC) | ADTP703TUW4 | 120 | 7.0% | Not Recommended |
| Cooper | AL Series | AAL06 | 120 | 44.0% | Flicker below 44% |
| Reverse Phase Dimmers (ELV) | | | | | |
| Lutron | Nova T | NTELV-600 | 120 | 46.0% | Flicker below 46% |
| Lutron | Diva | DVELV-300P | 120 | 47.0% | Flicker below 47% |
| Lutron | Maestro | MAELV-600 | 120 | 1.0% | |
| Lutron | Skylark | SELV-300P | 120 | 49.0% | Flicker below 49% |
| Leviton | Illumatech | IPE04-1LZ | 120 | 44.0% | Flicker below 44% |
| Lutron | Maestro | RRD-6NA | 120 | 1.0% | |
| Leviton | SureSlide | 6615-POW | 120 | 52.0% | Flicker below 52% |
| Leviton | Decora | DSE06-10Z | 120 | 40.0% | Flicker below 40% |
| Lutron | Caseta | PD-5NE | 120 | 52.0% | Flicker below 52% |
| Lutron | Homeworks | HRD-5NE | 120 | N/A | Flashing at high dimming level |
| Leviton | Renoir II | AWSMT-EBW | 120 | 49.0% | Flicker below 49% |
| Lutron | Grafik-Eye | GRX-3103-A-G | 120 | 47.0% | Flicker below 47% |
| Forward Phase Dimmers (TRIAC) | | | | | |
| Lutron | Maestro | MAEL-153M-WH | 120 | 5.0% | |
| Lutron | Diva | DVCL-153P | 120 | 6.0% | |
| Legrand | Adorne Paddle | ADPD453LW2 | 120 | 13.0% | |
| Lutron | Ariadni | AYCL-153PH | 120 | 3.0% | |
| Lutron | Skylark | SCL-153P-WH | 120 | 3.0% | |
| Lutron | Maestro | MA-600-WH | 120 | 3.0% | |
| Leviton | SureSlide | 6674-POW | 120 | 10.0% | Flicker below 10% |
| Lutron | Caseta | PD-6WCL | 120 | 5.0% | |
| Legrand | Harmony | HCL453PW | 120 | 3.0% | |
| Legrand | Radiant | RHCL453PW | 120 | 3.0% | |

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects Modern Forms's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to Modern Forms, and therefore Modern Forms cannot ensure future compatibility. For any questions on this report, please contact Modern Forms Customer Service at 1-866-810-6615 or customerservice@modernforms.com.